



SAFETY DATA SHEET

Preparation Date: Apr 04, 2019
Supersedes Date: Jul 05, 2018

Version Number: 02

SECTION 1

PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFIER

Product Name Unicut 500
Product ID Number DCT201060

RECOMMENDED USE AND RESTRICTIONS ON USE

Cutting Fluid

COMPANY IDENTIFICATION

Manufacturer Diversified Chemical Technologies, Inc.
15477 Woodrow Wilson, Detroit, MI 48238
(313) 867-5444

EMERGENCY TELEPHONE NUMBER

24 Hour Emergency Phone Number (Health & Safety; Transportation) CHEMTREC - (800) 424-9300

SECTION 2

HAZARDS IDENTIFICATION

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and Workplace Hazardous Materials Information System (WHMIS) 2015, and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

GHS CLASSIFICATION

Product has not been tested as a whole to determine its GHS classification. Hazard categories are based on individual ingredient hazard categories. Refer Section 16 for additional GHS Phrases.

GHS Hazard Class	GHS Hazard Category
Skin Sensitization	1
Aquatic Toxicity (Acute)	3
Aquatic Toxicity (Chronic)	3

GHS LABEL ELEMENTS

Pictogram



GHS Signal Word

Warning

GHS Hazard Phrases

H317 - May cause an allergic skin reaction.
H402 - Harmful to aquatic life.
H412 - Harmful to aquatic life with long lasting effects.

GHS Precaution Phrases

P261 - Avoid breathing mist or spray.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves and eye protection.

Product Name: Unicut 500

Preparation Date: Apr 04, 2019

GHS Response Phrases

P302+352 - IF ON SKIN: Wash with plenty of soap and water.
P333+313 - If skin irritation or rash occurs, seek medical advice/attention.
P362+364 - Take off contaminated clothing and wash it before reuse.

GHS Storage and Disposal Phrases

P501 - Dispose of contents/container to...*licensed professional waste disposal service or contact your regulatory department.*

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

CAS Number	Ingredients*	Percentage Range
64742-52-5	Mineral oil, petroleum distillates, hydrotreated heavy naphthenic	70 - 80

*Identity of other chemicals and/or exact percentage (concentration) has been withheld as a trade secret.

SECTION 4 FIRST AID MEASURES

IN CASE OF INHALATION

Remove from exposure and move to fresh air immediately. If breathing is difficult, give oxygen. Get medical aid. Do not use mouth-to-mouth resuscitation if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

IN CASE OF SKIN CONTACT

Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid if irritation develops or persists. Wash clothing before reuse.

IN CASE OF EYE CONTACT

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Assure adequate flushing by separating the eyelids with fingers. Get medical aid.

IN CASE OF INGESTION

Do NOT induce vomiting. If victim is conscious and alert, rinse mouth and drink 2-4 cupfuls of milk or water. Never give anything by mouth to an unconscious person. If swallowed, wash out mouth with water provided person is conscious. Get medical aid.

SIGNS AND SYMPTOMS OF EXPOSURE

The chemical, physical, and toxicological properties of the product are not investigated. To the best of our knowledge, based on ingredients, the most important known symptoms and effects are described in section 2.

NOTE TO PHYSICIAN

Treat symptomatically and supportively. It is advisable not to induce vomiting due to the risk of aspiration and it is not usually necessary unless a large amount has been ingested or it has been contaminated with another product.

SECTION 5 FIRE FIGHTING MEASURES

Flash Point	225 °F
Flash Point Method	PMCC

Explosive Limits	<i>LEL:</i> N/D	<i>UEL:</i> N/D
Auto Ignition Point	N/D	

SUITABLE EXTINGUISHING MEDIA

Use dry sand or earth to smother fire. Use extinguishing media appropriate to surrounding fire conditions. For small (incipient) fires, use media such as alcohol foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

Product Name: Unicut 500

Preparation Date: Apr 04, 2019

FIRE FIGHTING INSTRUCTIONS

As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Wear appropriate protective clothing to prevent contact with skin and eyes. Use water with caution and in flooding amounts. Contact with moisture or water may generate sufficient heat to ignite nearby combustible materials. Vapors may be heavier than air. They can spread along the ground and collect in low or confined areas. Containers may explode when heated.

FLAMMABLE PROPERTIES AND HAZARDS No data available.

SECTION 6 ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. National Response Center (24-HR Reporting): (800) 424-8802.

SAFETY PRECAUTIONS

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Vapors can accumulate in low areas. For industrial use only. Keep out of reach of children.

CONTAINMENT AND CLEANUP

Avoid runoff into storm sewers and ditches which lead to waterways. Clean up spills immediately, observing precautions. Absorb spill with inert material and place in closed containers for disposal. Ventilate area and wash spill site after material pickup is complete.

SECTION 7 HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING

Wash thoroughly after handling. Do not breathe dust, mist, or vapor. Do not get in eyes, on skin, or on clothing. Keep container tightly closed. Do not ingest or inhale. Use with adequate ventilation. Unvented containers may develop pressure – use with caution.

PRECAUTIONS TO BE TAKEN IN STORAGE

Keep container closed when not in use. Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances. Protect from freeze and high temperatures (>140 °F). Keep away from sparks, heat and flame. Do not mix with oxidizing materials.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

CAS #	Ingredients	OSHA TWA	ACGIH TWA	Other Limits
64742-52-5	Mineral oil* (regulated as mist only)	TWA: 5 mg/m3	TWA: 5 mg/m3; STEL: 10 mg/m3	N/A

ENGINEERING CONTROLS

The level of ventilation necessary will vary depending upon potential exposure conditions. Adequate ventilation should be provided so that exposure limits are not exceeded. If heavy misting is present, local exhaust ventilation should be considered in addition to general mechanical ventilation.

WORK/HYGIENIC/MAINTENANCE PRACTICES

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing separate from home laundry and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping. Do not store work clothing and protective equipment in the same locker as personal clothing.

PERSONAL PROTECTIVE EQUIPMENT

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal use.

Product Name: Unicut 500

Preparation Date: Apr 04, 2019

Respiratory Protection If vapors or mists are present and if engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, a NIOSH/MSHA approved respirator may be appropriate. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant respirator use. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Types of respirators to be considered for this material include: **Air-Purifying Half-Face Respirator with oil mist cartridges.**

Hand Protection Wear appropriate protective gloves to prevent skin exposure. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include: **Nitrile.**

Eye Protection Safety glasses are recommended. If splashing is likely, safety goggles or safety glasses with splash shield are recommended. Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and Body Protection No specific protective equipment is needed under normal use conditions. In general, the types of clothing to be considered for this material include: Long-sleeved shirt and pants, at a minimum.

OTHER PROTECTIVE EQUIPMENT Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear Brown
Physical State	Liquid
Odor	Petroleum
pH	N/A
Melting Point	N/A
Boiling Point	250 °F

Specific Gravity (water = 1)	0.91
Vapor Pressure	N/D
Viscosity (SUS)	225 @ 100 °F
Evaporation Rate (water = 1)	N/D
Volatile Organic Compounds (%)	0.6
Solubility in Water	Insoluble

SECTION 10 STABILITY / REACTIVITY

Chemical Stability *Unstable* [] *Stable* [X]

Conditions to Avoid Excess heat

Reactivity / Incompatibility Strong oxidizing agents, strong acids, strong bases

Hazardous Decomposition Material does not decompose at ambient temperature. Thermal decomposition can produce a variety of compounds, the nature of which will largely depend on the conditions bringing about decomposition. Incomplete combustion or thermal decomposition may be expected to generate such materials as: particulate matter and unburned, hydrocarbons; oxides of carbon, nitrogen; water vapor; and other unidentified organic and inorganic compounds.

Hazardous Reactions *Will occur* [] *Will not occur* [X]

SECTION 11 TOXICOLOGICAL INFORMATION

CARCINOGENICITY

Product is not tested for carcinogenicity. No components of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen, except as identified below;

IARC: Not Listed **ACGIH:** Not Listed **NTP:** Not Listed

PRODUCT TOXICOLOGICAL DATA

Product is not tested for classification under the following categories:

LD50 (Oral), LC50 (Inhalation), Dermal Toxicity (Skin), Skin Corrosion/Irritation, Serious Eye Damage/Irritation, Respiratory/ Skin Sensitization, Germ Cell Mutagenicity, Carcinogenicity, Reproductive Toxicity, STOT-single exposure, STOR-repeated exposure, Aspiration Hazard

Product Name: Unicut 500

Preparation Date: Apr 04, 2019

INGREDIENT TOXICOLOGICAL DATA

None of the ingredients above 1% concentration (0.1% for carcinogens) trigger the hazard rating or classify under the following categories, unless indicated below:

LD50 (Oral), LC50 (Inhalation), Dermal Toxicity (Skin), Skin Corrosion/Irritation, Serious Eye Damage/Irritation, Respiratory/ Skin Sensitization, Germ Cell Mutagenicity, Carcinogenicity, Reproductive Toxicity, STOT-single exposure, STOR-repeated exposure, Aspiration Hazard

CAS# 64742-52-5:

Mutagenicity:, Mutation test: Mutation in microorganisms., 10.00 UL/PLAT, Bacteria - Salmonella typhimurium,. Result: Behavioral: Convulsions or effect on seizure threshold. Gastrointestinal:Hypermotility, diarrhea. Nutritional and Gross Metabolic:Changes in:Body temperature increase.

Mutagenicity:, Mutation test: Mutation in microorganisms., 10.00 UL/PLAT, Bacteria -Salmonella typhimurium,. Result: Behavioral: Convulsions or effect on seizure threshold. Gastrointestinal:Hypermotility, diarrhea. Kidney, Ureter, Bladder:Other changes.

Acute toxicity, LD (Lethal dose), Oral, Rat, > 5.000 GM/KG. Result: Behavioral: Convulsions or effect on seizure threshold. Skin and Appendages: Skin: After systemic exposure: Dermatitis, other. Nutritional and Gross Metabolic:Changes in:Body temperature increase.

Acute toxicity, LD (Lethal dose), Skin, Species: Rabbit, > 5.000 GM/KG. Result:Behavioral: Somnolence (general depressed activity). Behavioral: Muscle contraction or spasticity. Lungs, Thorax, or Respiration:Dyspnea.

SECTION 12 ECOLOGICAL INFORMATION

General Ecological Information	N/AV.	Persistence and Degradability	N/AV
Bioaccumulative Potential	N/AV.	Mobility in Soil	N/AV

SECTION 13 DISPOSAL CONSIDERATIONS

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated Packaging	Dispose of as unused product.
Empty Containers	Clean empty containers of any residue per 40CFR261.7 guidelines and either recycle containers or dispose of in normal trash.

SECTION 14 TRANSPORT INFORMATION

	LAND (US DOT)	MARINE (IMDG)	AIR (IATA)
Proper Shipping Name	N/A		
Hazard Class	N/A		
ID Number	N/A		
Packaging Group	N/A		

Additional Information

DOT Quantity Limitation: N/A

DOT Label for Limited Quantities: N/A

SECTION 15 REGULATORY INFORMATION

EPA SARA (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986) LISTS

[302 (EHS) TPQ, 304 CERCLA RQ, 304 EHS RQ, 313 (TRI)]

None of the ingredients above 1% concentration (0.1% for carcinogens) are identified in the lists:

SARA TITLE III SECTION 311/312 CATEGORIZATION (40 CFR 370) – see Section 2 for hazard categories in accordance with EPA’s June 2016 final rule on amendments to hazardous chemical inventory reporting

Product Name: Unicut 500

Preparation Date: Apr 04, 2019

STATE AND OTHER US EPA REGULATIONS

California Prop. 65 - N/A

NATIONAL INVENTORIES

TSCA	Yes
CAA HAP, ODC	No
CWA NPDES	No
CEPA (DSL/NDL)	Yes
KECI	N/D

AICS	N/D
IECSC	N/D
EINECS	N/D
ENCS	N/D
PICCS	N/D

SECTION 16 OTHER INFORMATION

NFPA RATING Health (Blue): 1 Flammability (Red): 0 Reactivity (Yellow): 0 Specific Hazard(s) (White): None

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS

EU format MSDS to GHS format SDS; Ingredient/percentage

02: Formulation update

USER RESPONSIBILITY It is the user's responsibility to determine the suitability and adopt precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of this product.

PREPARED BY

Environmental, Health and Safety Department of Diversified Chemical Technologies, Inc. and Subsidiaries

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE RELIABLE AND ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.