



SAFETY DATA SHEET

Preparation Date: Dec 16, 2019
Supersedes Date:

Version Number: 00

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFIER

Product Name Unicool 427
Product ID Number DCT201810

RECOMMENDED USE AND RESTRICTIONS ON USE

Machining, Grinding, and Tapping Fluid

COMPANY IDENTIFICATION

Manufacturer Diversified Chemical Technologies, Inc.
15477 Woodrow Wilson, Detroit, MI 48238
(313) 867-5444

EMERGENCY TELEPHONE NUMBER

24 Hour Emergency Phone Number (Health & Safety; Transportation) CHEMTREC - (800) 424-9300

SECTION 2 HAZARDS IDENTIFICATION

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and Workplace Hazardous Materials Information System (WHMIS) 2015, and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

GHS CLASSIFICATION

Product has not been tested as a whole to determine its GHS classification. Hazard categories are based on individual ingredient hazard categories. Refer Section 16 for additional GHS Phrases.

| GHS Hazard Class | GHS Hazard Category |
|-----------------------------------|---------------------|
| Serious Eye Damage/Eye Irritation | 2A |
| Skin Corrosion/Irritation | 3 |
| Skin Sensitization | 1B |

GHS LABEL ELEMENTS

Pictogram



GHS Signal Word

WARNING

GHS Hazard Phrases

H316 - Causes mild skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.

GHS Precaution Phrases

P261 - Avoid breathing mist or spray.
P264 - Wash hands thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P280 - Wear protective gloves and eye protection.

Product Name: Unicool 427

Preparation Date: Dec 16, 2019

GHS Response Phrases

P302+352 - IF ON SKIN: Wash with plenty of soap and water.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+313 - If skin irritation or rash occurs, seek medical advice/attention.

P337+313 - If eye irritation persists, get medical advice/attention.

P362+364 - Take off contaminated clothing and wash it before reuse.

GHS Storage and Disposal Phrases

P501 - Dispose of contents/container to...*licensed professional waste disposal service or contact your regulatory department.*

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

| CAS Number | Ingredients* | Percentage Range |
|------------|-------------------------------------|------------------|
| 64742-52-5 | Mineral oil, petroleum distillates, | 15 - 20 |
| 102-71-6 | Triethanolamine | 10 - 15 |
| 112-34-5 | Diethylene glycol monobutyl ether | 1 - 3 |

*Identity of other chemicals and/or exact percentage (concentration) has been withheld as a trade secret.

SECTION 4 FIRST AID MEASURES

IN CASE OF INHALATION

Remove from exposure and move to fresh air immediately. If breathing is difficult, give oxygen. Get medical aid. Do not use mouth-to-mouth resuscitation if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

IN CASE OF SKIN CONTACT

Flush skin with plenty of water while removing contaminated clothing and shoes. Get medical aid if irritation develops or persists. Wash clothing before reuse.

IN CASE OF EYE CONTACT

Flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Assure adequate flushing by separating the eyelids with fingers. Get medical aid.

IN CASE OF INGESTION

Do NOT induce vomiting. If victim is conscious and alert, rinse mouth and drink 2-4 cupfuls of milk or water. Never give anything by mouth to an unconscious person. If swallowed, wash out mouth with water provided person is conscious. Get medical aid.

SIGNS AND SYMPTOMS OF EXPOSURE

The chemical, physical, and toxicological properties of the product are not investigated. To the best of our knowledge, based on ingredients, the most important known symptoms and effects are described in section 2.

NOTE TO PHYSICIAN

Treat symptomatically and supportively. It is advisable not to induce vomiting due to the risk of aspiration and it is not usually necessary unless a large amount has been ingested or it has been contaminated with another product.

SECTION 5 FIRE FIGHTING MEASURES

| | |
|---------------------------|------|
| Flash Point | None |
| Flash Point Method | N/A |

| | | |
|----------------------------|----------|----------|
| Explosive Limits | LEL: N/D | UEL: N/D |
| Auto Ignition Point | N/D | |

Product Name: Unicool 427

Preparation Date: Dec 16, 2019

SUITABLE EXTINGUISHING MEDIA

Use dry sand or earth to smother fire. Use extinguishing media appropriate to surrounding fire conditions. For small (incipient) fires, use media such as alcohol foam, dry chemical, or carbon dioxide. For large fires, apply water from as far as possible. Use very large quantities (flooding) of water applied as a mist or spray; solid streams of water may be ineffective. Cool all affected containers with flooding quantities of water.

FIRE FIGHTING INSTRUCTIONS

As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Wear appropriate protective clothing to prevent contact with skin and eyes. Use water with caution and in flooding amounts. Contact with moisture or water may generate sufficient heat to ignite nearby combustible materials. Vapors may be heavier than air. They can spread along the ground and collect in low or confined areas. Containers may explode when heated

FLAMMABLE PROPERTIES AND HAZARDS No data available.

SECTION 6 ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. National Response Center (24-HR Reporting): (800) 424-8802.

SAFETY PRECAUTIONS

For industrial use only. Keep out of reach of children.
Use personal protective equipment. During large spills - Avoid breathing vapors, mist or gas; Ensure adequate ventilation; Vapors can accumulate in low areas.

CONTAINMENT AND CLEANUP

Avoid runoff into storm sewers and ditches which lead to waterways. Clean up spills immediately, observing precautions. Absorb spill with inert material and place in closed containers for disposal. Ventilate area and wash spill site after material pickup is complete.

SECTION 7 HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING

Wash thoroughly after handling. Use caution; floors may be slippery if material is spilled. Avoid breathing mist or vapor – use only in a well-ventilated area. Do not get in eyes, on skin, or on clothing. Keep container tightly closed. Do not ingest. Unvented containers may develop pressure – use with caution.

PRECAUTIONS TO BE TAKEN IN STORAGE

Keep container closed when not in use. Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances. Protect from freeze and high temperatures (>140 °F).

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

| CAS # | Ingredients | OSHA TWA | ACGIH TWA | Other Limits |
|----------|-----------------|----------|--------------|--------------|
| 102-71-6 | Triethanolamine | N/A | TLV: 5 mg/m3 | N/A |

ENGINEERING CONTROLS

The level of ventilation necessary will vary depending upon potential exposure conditions. Adequate ventilation should be provided so that exposure limits are not exceeded. If heavy misting is present, local exhaust ventilation should be considered in addition to general mechanical ventilation.

Product Name: Unicool 427

Preparation Date: Dec 16, 2019

WORK/HYGIENIC/MAINTENANCE PRACTICES

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing separate from home laundry and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping. Do not store work clothing and protective equipment in the same locker as personal clothing.

PERSONAL PROTECTIVE EQUIPMENT

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal use.

Respiratory Protection No protective equipment is needed under normal use conditions. If vapors or mists are present and if engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, a NIOSH/MSHA approved respirator meeting OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements may be appropriate.

Hand Protection Wear appropriate protective gloves to prevent skin exposure. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include: Nitrile.

Eye Protection Safety glasses are recommended. If splashing is likely, safety goggles or safety glasses with splash shield are recommended. Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and Body Protection No specific protective equipment is needed under normal use conditions. In general, the types of clothing to be considered for this material include: Long-sleeved shirt and pants, at a minimum.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

| | |
|-----------------------|--------------|
| Appearance | Clear golden |
| Physical State | Liquid |
| Odor | Slight Amine |
| pH | 9.81 |
| Melting Point | N/A |
| Boiling Point | N/A |

| | |
|---------------------------------------|----------|
| Specific Gravity (water = 1) | 1.01 |
| Vapor Pressure | N/D |
| Viscosity (SUS) | N/D |
| Evaporation Rate (water = 1) | N/D |
| Volatile Organic Compounds (%) | 15.2 |
| Solubility in Water | Complete |

SECTION 10 STABILITY / REACTIVITY

Chemical Stability *Unstable* [] *Stable* [X]
Conditions to Avoid None known
Reactivity / Incompatibility Strong oxidizing agents, acids
Hazardous Decomposition Material does not decompose at ambient temperature. Thermal decomposition can produce a variety of compounds, the nature of which will largely depend on the conditions bringing about decomposition. Incomplete combustion or thermal decomposition may be expected to generate such materials as: particulate matter and unburned, hydrocarbons; oxides of carbon; water vapor; and other unidentified organic and inorganic compounds.
Hazardous Reactions *Will occur* [] *Will not occur* [X]

SECTION 11 TOXICOLOGICAL INFORMATION

CARCINOGENICITY
 Product is not tested for carcinogenicity. No components of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen, except as identified below;
IARC: Not Listed **ACGIH:** Not Listed **NTP:** Not Listed

Product Name: Unicool 427

Preparation Date: Dec 16, 2019

PRODUCT TOXICOLOGICAL DATA

Product is not tested for classification under the following categories:

LD50 (Oral), LC50 (Inhalation), Dermal Toxicity (Skin), Skin Corrosion/Irritation, Serious Eye Damage/Irritation, Respiratory/ Skin Sensitization, Germ Cell Mutagenicity, Carcinogenicity, Reproductive Toxicity, STOT-single exposure, STOR-repeated exposure, Aspiration Hazard

INGREDIENT TOXICOLOGICAL DATA

None of the ingredients above 1% concentration (0.1% for carcinogens) trigger the hazard rating or classify under the following categories, unless indicated below:

LD50 (Oral), LC50 (Inhalation), Dermal Toxicity (Skin), , Serious Eye Damage/Irritation, Respiratory/ Skin Sensitization, Germ Cell Mutagenicity, Carcinogenicity, Reproductive Toxicity, STOT-single exposure, STOR-repeated exposure, Aspiration Hazard

Skin Corrosion/Irritation: 112-34-5, Diethylene glycol monobutyl ether: Result: Tumorigenic:Tumors at site or application. Irritating to eyes. (OECD Test Guideline 405)

SECTION 12 ECOLOGICAL INFORMATION

| | | | |
|---------------------------------------|-------|--------------------------------------|------|
| General Ecological Information | N/AV. | Persistence and Degradability | N/AV |
| Bioaccumulative Potential | N/AV. | Mobility in Soil | N/AV |

SECTION 13 DISPOSAL CONSIDERATIONS

Not RCRA hazardous; however, if this product is altered, it is the responsibility of the user to determine whether the material meets the criteria for hazardous waste at the time of disposal. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification, and disposal. Contact a licensed professional waste disposal service to dispose of this material. Follow all applicable federal, state, local and provincial regulations. Deposit of liquid in landfill is strictly regulated (40 CFR 265.314).

Empty Containers

Clean empty containers of any residue per 40CFR261.7 guidelines and either recycle containers or dispose of in normal trash.

SECTION 14 TRANSPORT INFORMATION

| | LAND (US DOT) | MARINE (IMDG) | AIR (IATA) |
|-----------------------------|---------------|---------------|------------|
| Proper Shipping Name | N/A | | |
| Hazard Class | N/A | | |
| ID Number | N/A | | |
| Packaging Group | N/A | | |

Additional Information

DOT Quantity Limitation: N/A

DOT Label for Limited Quantities: N/A

SECTION 15 REGULATORY INFORMATION

EPA SARA (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986) LISTS

[302 (EHS) TPQ, 304 CERCLA RQ, 304 EHS RQ, 313 (TRI)]

None of the ingredients above 1% concentration and 0.1% for carcinogens are identified in the lists, except

CAS 112-34-5; Diethylene glycol monobutyl ether – S313 (TRI) Cat N230

SARA TITLE III SECTION 311/312 CATEGORIZATION (40 CFR 370) – see Section 2 for hazard categories in accordance with EPA’s June 2016 final rule on amendments to hazardous chemical inventory reporting

Product Name: Unicool 427

Preparation Date: Dec 16, 2019

STATE AND OTHER US EPA REGULATIONS

California Prop. 65 - N/A

SECTION 16

OTHER INFORMATION

NFPA RATING Health (Blue): 1 Flammability (Red): 0 Reactivity (Yellow): 0 Specific Hazard(s) (White): None

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS

None

USER RESPONSIBILITY It is the user's responsibility to determine the suitability and adopt precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of this product.

PREPARED BY

Environmental, Health and Safety Department of Diversified Chemical Technologies, Inc. and Subsidiaries

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE RELIABLE AND ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.